

DRILLS(SPECIFICATIONS)



MODEL NO.	Avg.Air Consumption m ³ /min (CFM)	Max.Air Consumption m ³ /min (CFM)	Output (Watt)	Vibration (m/S ²)	Noise Level dB pressure(power)	Weight Body (gs)	Overall Length (mm)	Height (mm)	Width (mm)	Air Inlet Size (NPT)	Hose Size mm(in)	Free Speed (r.p.m)	Drilling Cap mm (in)	Chuck Size mm (in)	Spindle Size	Chuck
SI-2015AD	0.13 (4)	0.50 (18)	380	<2.5	89 (100)	767	212	44.5	44.5	1/4	10 (3/8)	4,500	6 (1/4)	10 (3/8)	3/8-24UNF	22BA
SI-5100	0.12 (4)	0.48 (17)	380	<2.5	87 (93)	882	187	145	44	1/4	10 (3/8)	5,000	6 (1/4)	10 (3/8)	3/8-24UNF	22BA
SI-5200	0.12 (4)	0.49 (17)	380	<2.5	84 (93)	1,168	228	145	44.5	1/4	10 (3/8)	500	13 (1/2)	13 (1/2)	3/8-24UNF	31902
SI-5300	0.12 (4)	0.48 (17)	380	<2.5	87 (93)	892	187	145	44	1/4	10 (3/8)	2,200	10 (3/8)	10 (3/8)	3/8-24UNF	22BA
SI-5305	0.13 (4)	0.50 (18)	300	<2.5	91 (102)	994	187	152	42	1/4	10 (3/8)	2,000	10 (3/8)	10 (3/8)	3/8-24UNF	22BA
SI-5305-8	0.13 (4)	0.50 (18)	300	<2.5	91 (102)	1,186	220	152	42	1/4	10 (3/8)	800	13 (1/2)	13 (1/2)	3/8-24UNF	31902
SI-5355	0.10 (4)	0.40 (14)	195	<2.5	83 (94)	937	205	90	41	1/4	10 (3/8)	1,200	10 (3/8)	10 (3/8)	3/8-24UNF	22BA
SI-5500	0.10 (4)	0.40 (14)	300	<2.5	86 (97)	796	180	143	42	1/4	10 (3/8)	2,600	10 (3/8)	10 (3/8)	3/8-24UNF	31904
SI-5505	0.11 (4)	0.45 (16)	158	<2.5	86 (99)	750	153	147	42	1/4	10 (3/8)	1,800	10 (3/8)	10 (3/8)	3/8-24UNF	LX-10