

IMPACT DRIVERS(SPECIFICATIONS)



MODEL NO.	Avg. Air Consumption m ³ /min (CFM)	Max. Air Consumption m ³ /min (CFM)	Output (Watt)	Vibration (m/S ²)	Noise Level d B pressure(power)	Weight (gs)	Overall Length (mm)	Height (mm)	Width (mm)	Air Inlet Size (NPT)	Hose Size mm(in)	Free Speed (r.p.m)	Drive	Shank Size mm (in)	Bolt Cap mm (in)	Max Torque Nm (lb-ft)	Clutch Type
SI-1051	0.08 (3)	0.31 (11)	136	4.1	84 (97)	553	162	60	36	1/4	10 (3/8)	10,000	Female Hex	6.35 (1/4)	5 (3/16)	33 (24)	Double Hammer
SI-1060	0.12 (4)	0.46 (16)	180	4.0	95 (105)	871	208	46	41	1/4	10 (3/8)	10,000	Female Hex	6.35 (1/4)	6 (1/4)	41 (30)	Double Hammer
SI-1061	0.10 (4)	0.42 (15)	180	4.5	90 (100)	861	188	51	42	1/4	10 (3/8)	10,000	Female Hex	6.35 (1/4)	6 (1/4)	41 (30)	Double Hammer
SI-1065	0.12 (4)	0.46 (16)	180	5.0	88 (89)	1,034	172	182	41	1/4	10 (3/8)	13,500	Female Hex	6.35 (1/4)	6 (1/4)	41 (30)	Double Hammer
SI-1365D	0.15 (5)	0.60 (21)	300	7.94	80 (90)	1,337	144	194	53	1/4	10 (3/8)	10,000	Female Hex	6.35 (1/4)	8 (5/16)	88 (65)	Double Hammer
SI-1370D	0.15 (5)	0.60 (21)	300	8.91	80 (90)	1,266	247	53	50	1/4	10 (3/8)	10,000	Female Hex	6.35 (1/4)	8 (5/16)	88 (65)	Double Hammer