

# RATCHET WRENCHES(SPECIFICATIONS)



MODEL NO.	Avg.Air Consumption m <sup>3</sup> /min (CFM)	Max.Air Consumption m <sup>3</sup> /min (CFM)	Output (Watt )	Vibration (m/S <sup>2</sup> )	Noise Level d B pressure(power)	Weight (gs)	Overall Length (mm)	Height (mm)	Width (mm)	Air Inlet Size (NPT)	Hose Size mm(in)	Free Speed (r.p.m)	Drive	Shank Size mm (in)	Bolt Cap mm (in)	Max Torque Nm (lb-ft)	Torque Range Nm (lb-ft)
SI-1200B	0.09 (3)	0.31 (11)	160	3.3	82 (93)	509	169	35.5	34	1/4	6 (1/4)	250	sq	6.35 (1/4)	6 (1/4)	28 (20)	7-28 (5-20)
SI-1205B	0.09 (3)	0.31 (11)	160	3.3	82 (93)	511	169	35.5	34	1/4	6 (1/4)	250	sq	9.5 (3/8)	6 (1/4)	28 (20)	7-28 (5-20)
SI-1207	0.09 (3)	0.31 (11)	160	3.3	83 (93)	535	170	39	38	1/4	6 (1/4)	250	sq	6.35 (1/4)	6 (1/4)	28 (20)	7-28 (5-20)
SI-1208	0.09 (3)	0.31 (11)	160	3.3	82 (93)	540	170	39	38	1/4	6 (1/4)	250	sq	9.5 (3/8)	6 (1/4)	28 (20)	7-28 (5-20)
SI-1288S	0.10 (3)	0.32 (11)	160	3.3	82 (93)	557	215	37	35	1/4	6 (1/4)	450	Hex	17 (43/64)	6 (1/4)	28 (20)	7-28 (5-20)
SI-1320A	0.11 (4)	0.38 (13)	300	8.5	92 (102)	1,170	266	43	40	1/4	10 (3/8)	160	sq	9.5 (3/8)	10 (3/8)	68 (50)	13-60 (10-45)
SI-1325A	0.11 (4)	0.38 (13)	300	8.5	92 (102)	1,182	266	43	40	1/4	10 (3/8)	160	sq	12.7 (1/2)	10 (3/8)	68 (50)	13-60 (10-45)
SI-1340A	0.11 (4)	0.38 (13)	300	8.5	92 (102)	1,157	278	41.5	40	1/4	10 (3/8)	170	sq	9.5 (3/8)	10 (3/8)	68 (50)	13-60 (10-45)
SI-1345A	0.11 (4)	0.38 (13)	300	8.5	92 (102)	1,163	266	43	40	1/4	10 (3/8)	170	sq	12.7 (1/2)	10 (3/8)	68 (50)	13-60 (10-45)
SI-1435	0.16 (5)	0.52 (18)	400	8.8	94 (106)	1,950	367	51.5	48	1/4	10 (3/8)	140	sq	12.7 (1/2)	12 (1/2)	132 (97)	14-118 (20-90)